

## HORIZONTAL PUMP mod. ID/OL 2 Open Top

## FOR CEMENT GROUT, COLLOIDAL GROUT AND CHEMICAL GROUT



The horizontal grout pump mod. ID/OL- 2 designed for modular assembly has been **recently improved with upgrades on:** 



lighter chassis (more space available for maintenance); hydraulic oil tank (more capacity); heat exchanger (higher capacity); hydraulic plant (more simple and easier for maintenance), maintaining anyway all main spare parts characteristic of previous version. Lightweight, compact, easy to use in confined spaces and in areas with difficult access solves the most difficult operational situations

The grout pump can be used as: simple pump, for grout filling or grout transferring, for micropiles, anchors, nails, etc..

The new ID/OL-2 is equipped with a distributor suitable for its use on injections jobs with sleeve grout breakage phases.

This pump is therefore provided for two different working regimes, with different performance: maximum flow rate operated at low pressure (LP) and the maximum pressure operation with highpressure (HP), for sleeve grout breakage. The transition from HP to LP is manually operated through a specific switch located on the electrical control panel.

Two or more pumps can be installed in series fed by a single agitator for the simultaneous injection of several holes.

The ID/OL 2 can be fitted with a data logger DPV for displaying and recording of grouting parameters (pressure, flow rate and volume).

The data can be downloaded through USB. The system is designed to manage the injection following the parameters previously set.

| TECHNICAL SHEETS         |              | ID/OL 2          |
|--------------------------|--------------|------------------|
| Piston diameter          | mm.          | 85               |
| Piston stroke            | mm.          | 126              |
| Max strokes n.           | strokes/min. | 75               |
| Pressure (LP) adjustable | bar          | 0 - 55           |
| Delivery (LP) adjustable | litri/min.   | 0 - 60           |
| Maximum pressure (HP)    | bar          | 90               |
| Delivery (HP)            | litri/min.   | 9                |
| Inlet Mouth              | gas          | 1"1/2            |
| Outlet Mouth             | gas          | <sup>3</sup> /4" |
| Electric Power           | kW           | 5,5              |
| Length                   | mm.          | 1050             |
| Width                    | mm.          | 690              |
| Height                   | mm.          | 1160             |
| Weight                   | kg.          | 290              |

(All data, illustrations and features of this prospectus are subject to change without notice or liability)