

HORIZONTAL GROUT PUMP



mod. ID/OL-7

GEOTECHNICAL EQUIPMENT

FOR CEMENT, COLLOIDAL AND CHEMICAL GROUT



The horizontal pump mod. ID/OL-7 is a grout pump designed for modular assembly. Lightweight, compact, easy to use in confined spaces and in places difficult to access, in the best way solves even the most difficult operational situations. The grout pump can be used for grout transferring, minipiles, anchors, nails, etc.. More pumps can be installed in series fed by a single agitator for the simultaneous injection of more holes or for transferring of large quantities of grout (Backfilling Application).

TECHNICAL DATA SHEET		ID/OL - 7
Piston diameter	mm.	115
Piston stroke	mm.	250
Max strokes number	strokes/min.	42
Pressure adjustable	bar	180
Flow-rate adjustable	litri/min.	180
Pressure and flow-rate not contemporaneous		
Inlet Diam.	gas	3"
Outlet Mouth	gas	1 1/4"
Electric Power	kW	22,0
Length	mm.	1.650
Width	mm.	950
Height	mm.	1.610
Weight	kg.	1.080

(All data, illustrations and features of this brochure are subject to change without notice or liability)



CLIVIO s.r.l.

via Ponte Taro, 28/A - 43015 Noceto PR - Italy

tel +39 0521 628919 - fax +39 0521 621661 - www.cliviosrl.it - info@cliviosrl.it